

Construction (n x mm ²)	Outer diameter (ca. mm)	AI number (kg/km)	Cable weight (ca. kg/km)
1 x 25 RM	11.6	73	196
1 x 35 RM	12.6	102	234
1 x 50 RM	14.3	145	311
1 x 70 RM	16.0	203	379
1 x 95 RM	18.0	275	496
1 x 120 RM	19.9	348	592
1 x 150 RM	21.5	435	695
1 x 185 RM	24.3	537	929
1 x 240 RM	27.4	696	1189
1 x 300 RM	29.6	870	1428
1 x 400 RM	32.5	1160	1752
2 x 16 RM	17.2	93	390
3 x 25 RM	22.2	218	718
3 x 35 RM	24.3	305	877
3 x 35 SM / 16RM	24.0	351	391
3 x 50 SM	25.4	435	835
3 x 50 SM / 25RM	27.4	508	972
3 x 70 SM	28.6	609	1116
3 x 95 SM	33.3	827	1481
3 x 95 SM / 70SM	37.9	1030	1808
3 x 120 SM	36.7	1044	1782
3 x 120 SM / 70SM	39.1	1247	2090
3 x 150 SM	39.0	1305	2097
3 x 150 SM / 70SM	44.2	1508	2421
3 x 185 SM	40.8	1610	2582
3 x 185 SM/ 95 SM	47.9	1885	3257
3 x 240 SM	46.6	2088	3410
3 x 240 SM/ 120 SM	53.9	2436	4137
3 x 300 SM	53.4	2610	4150
4 x 16 RM	20.2	186	569
4 x 25 RM	24.7	290	873
4 x 35 RM	27.8	406	1216
4 x 50 SM	27.5	580	1063
4 x 70 SM	31.4	812	1411
4 x 95 SM	38.2	1102	1930
4 x 120 SM	40.5	1392	2308
4 x 150 SM	43.9	1740	2730
4 x 185 SM	50.8	2146	3650
4 x 240 SM	57.4	2784	4690
4 x 300 SM	61.3	3480	5830
5 x 16 RM	22.2	232	688
5 x 25 RM	27.1	363	1058
5 x 35 RM	30.4	508	1317
5 x 50 RM	33.6	725	1680
5 x 70 RM	38.8	1015	2287
5 x 95 RM	44.7	1378	3037