

Construction (n x mm <sup>2</sup> )	Outer diameter (ca. mm)	Cu number (kg/km)	Weight (ca. kg/km)
1 x 4 RE	7.0	38	87
1 x 6 RE	7.5	58	106
1 x 10 RE	8.4	96	152
1 x 16 RM	9.6	154	215
1 x 25 RM	11.4	240	320
1 x 35 RM	12.0	336	406
1 x 50 RM	13.6	480	539
1 x 70 RM	15.5	672	751
1 x 95 RM	24.0	912	998
1 x 120 RM	19.1	1152	1243
1 x 150 RM	20.7	1440	1533
1 x 185 RM	23.2	1813	1870
1 x 240 RM	25.7	2304	2386
1 x 300 RM	27.7	2880	2970
2 x 1.5 RE	8.8	29	117
2 x 2.5 RE	9.5	48	149
2 x 4 RE	11.3	77	222
2 x 6 RE	12.2	115	273
2 x 10 RE	14.0	192	418
2 x 16 RE	16.2	307	601
2 x 25 RM	19.8	480	880
2 x 50 RM	25.5	960	1544
3 x 1.5 RE	9.2	43	135
3 x 2.5 RE	10.0	72	177
3 x 4 RE	11.7	115	253
3 x 6 RE	12.7	173	237
3 x 10 RE	14.5	288	473
3 x 10 RM	14.7	288	472
3 x 16 RE	16.6	461	686
3 x 16 RM	17.1	461	684
3 x 25 RM	20.1	720	1025
3 x 25 RM/16RE	20.1	874	1196
3 x 35 RM	22.8	1008	1369
3 x 35 SM/16RE	25.1	1162	1396
3 x 50 RM	26.4	1440	1849
3 x 50 SM/25RM	28.8	1680	1941
3 x 70 SM/35RM	32.4	2352	2709
3 x 95 SM/50SM	34.4	3216	3705
3 x 120 SM/70SM	38.8	4128	4695
3 x 150 SM/70SM	42.3	4992	5635
3 x 185 SM	45.2	5328	5703
3 x 185 SM/95SM	50.0	6240	7260
3 x 240 SM	49.3	6912	8754
3 x 240 SM/120SM	52.7	8064	8486
3 x 300 SM/150SM	57.5	10080	11185
4 x 1.5 RE	9.8	58	156
4 x 2.5 RE	10.6	96	202
4 x 4 RE	12.9	154	308
4 x 6 RE	13.8	230	394
4 x 10 RE	15.7	384	592
4 x 10 RM	16.2	384	597
4 x 16 RE	18.2	614	861
4 x 16 RM	19.0	614	879
4 x 25 RM	23.7	960	1352
4 x 35 SM	25.1	1344	1656
4 x 50 SM	28.8	1920	2220
4 x 70 SM	33.4	2688	3159
4 x 95 SM	38.1	3648	4261
4 x 120 SM	40.4	4608	5270
4 x 150 SM	44.2	5760	6136
4 x 185 SM	50.0	7104	8217

4 x 240 SM	56.1	9216	9612
4 x 300 SM	60.8	11520	13121
5 x 1.5 RE	10.6	72	186
5 x 2.5 RE	11.6	120	254
5 x 4 RE	14.0	192	390
5 x 6 RE	15.4	288	504
5 x 10 RE	17.7	480	748
5 x 10 RM	18.0	480	732
5 x 16 RE	20.3	768	1053
5 x 16 RM	21.3	768	1086
5 x 25 RM	26.1	1200	1679
5 x 35 RM	29.1	1680	2299
5 x 50 RM	33.1	2400	3084
5 x 70 RM	37.3	3360	4084
5 x 95 RM	43.1	4560	5544